

Appl. No. 10/644,280  
Amdt. dated Mar. 21, 2006  
Reply to Off. Act. dated Dec. 23, 2005

**Amendments to the Claims:**

The following listing of claims replaces all prior versions and listings of claims in the application:

**Listing of Claims:**

Claims 1-5 (cancelled)

Claim 6 (currently amended): A cable tray for use in a cable tray system in which at least two cable trays are connected together with at least one fastener, the cable tray comprising:

a cable support assembly having a weight-bearing base portion and a plurality of sidewalls, the sidewalls being connected to longitudinal edges of the base portion and extending in a common direction perpendicular to the base portion, the base portion defining a plurality of open ends of the cable support assembly;

a connector receiving member connected to the base portion of the cable support assembly proximate a first open end of the cable support assembly, the connector receiving member including two parallel sections separated by a space and extending transversely across at least part of a width of the base portion, the two parallel sections of the connector receiving member being arranged to at least receive at least a portion of a first fastener in the space therebetween; and

a connector receiving element connected to the base portion of the cable support assembly proximate a second open end of the cable support assembly, the connector receiving element including two parallel sections separated by a space and extending longitudinally beyond the second open end of the cable support assembly, the two parallel sections of the connector receiving element being arranged to at least receive at least a portion of a second fastener therebetween, The cable tray of claim 4, wherein the connector receiving element further including [[includes]] a loop member interconnecting common ends of the two parallel sections of the connector receiving element, such that the connector receiving element forms a looping element that extends beyond the second open end of the cable support assembly.

Appl. No. 10/644,280  
Amdt. dated Mar. 21, 2006  
Reply to Off. Act. dated Dec. 23, 2005

Claim 7 (currently amended): A cable tray for use in a cable tray system in which at least two cable trays are connected together with at least one fastener, the cable tray comprising:

a cable support assembly having a weight-bearing base portion and a plurality of sidewalls, the sidewalls being connected to longitudinal edges of the base portion and extending in a common direction perpendicular to the base portion, the base portion defining a plurality of open ends of the cable support assembly;

a connector receiving member connected to the base portion of the cable support assembly proximate a first open end of the cable support assembly, the connector receiving member including two parallel sections separated by a space and extending transversely across at least part of a width of the base portion, the two parallel sections of the connector receiving member being arranged to at least receive at least a portion of a first fastener in the space therebetween;

a connector receiving element connected to the base portion of the cable support assembly proximate a second open end of the cable support assembly, the connector receiving element including two parallel sections separated by a space and extending longitudinally beyond the second open end of the cable support assembly, the two parallel sections of the connector receiving element being arranged to at least receive at least a portion of a second fastener therebetween; and

~~The cable tray of claim 4, further comprising~~ a second connector receiving element connected to the base portion of the cable support assembly proximate the first open end of the cable support assembly, the second connector receiving element including two parallel sections separated by a space and extending longitudinally beyond the first open end of the cable support assembly, the two parallel sections of the second connector receiving element being arranged to at least receive at least a portion of a third fastener therebetween.

Claim 8 (cancelled)

Claim 9 (previously presented): The cable tray of claim 7, wherein the second connector receiving element is positioned directly across from the connector receiving member along the width of the base portion of the cable support assembly and is further positioned diagonally

Appl. No. 10/644,280  
Amdt. dated Mar. 21, 2006  
Reply to Off. Act. dated Dec. 23, 2005

across from the connector receiving element along a length of the base portion of the cable support assembly.

Claims 10-11 (cancelled)

Claim 12 (previously presented): A cable tray system comprising:

a first cable tray including a first cable support assembly and a connector receiving member, the first cable support assembly having a weight-bearing base portion and a plurality of sidewalls, the sidewalls of the first cable support assembly being connected to longitudinal edges of the base portion of the first cable support assembly and extending in a common direction perpendicular to the base portion of the first cable support assembly, the base portion of the first cable support assembly defining a plurality of open ends of the first cable support assembly, the connector receiving member being connected to at least one of the base portion and a sidewall of the first cable support assembly proximate an open end of the first cable support assembly, the connector receiving member including two parallel wire sections separated by a space and extending transversely across at least part of a width of the base portion or the sidewall of the first cable support assembly;

a second cable tray including a second cable support assembly and a connector receiving element, the second cable support assembly having a weight-bearing base portion and a plurality of sidewalls, the sidewalls of the second cable support assembly being connected to longitudinal edges of the base portion of the second cable support assembly and extending in a common direction perpendicular to the base portion of the second cable support assembly, the base portion of the second cable support assembly defining a plurality of open ends of the second cable support assembly, the connector receiving element being connected to at least one of the base portion and a sidewall of the second cable support assembly, proximate an open end of the second cable support assembly, the connector receiving element including two parallel wire sections separated by a space and extending longitudinally beyond the open end of the second cable support assembly, wherein the space between the two parallel wire sections of the connector receiving element of the second cable tray overlaps the space between the two parallel

Appl. No. 10/644,280  
Amdt. dated Mar. 21, 2006  
Reply to Off. Act. dated Dec. 23, 2005

wire sections of the connector receiving member of the first cable tray when the second cable tray is positioned adjacent the first cable tray; and

a fastener adapted to pass through the connector receiving member of the first cable tray and the connector receiving element of the second cable tray to secure the two parallel wire sections of the connector receiving element to the two parallel wire sections of the connector receiving member.

Claim 13 (previously presented): The cable tray system of claim 12, wherein at least one of the first cable support assembly and the second cable support assembly is pre-formed into a shape having at least one interior angle, wherein said shape allows for intersection of a plurality of cable trays at angles other than 180 degrees.

Claim 14 (previously presented): The cable tray system of claim 12, wherein at least one of the two parallel wire sections of the connector receiving member includes an insulated portion and an electrically conductive portion, wherein at least one of the two parallel wire sections of the connector receiving member includes an insulated portion and an electrically conductive portion, and wherein the electrically conductive portion of the two parallel wire sections of the connector receiving member engages the electrically conductive portion of the two parallel wire sections of the connector receiving element when the connector receiving member is secured to the connector receiving element by the fastener, thereby providing electrical continuity between the first cable tray and the second cable tray.

Claim 15 (previously presented): The cable tray system of claim 14, wherein the electrically conductive portion of the two parallel wire sections of the connector receiving member and the electrically conductive portion of the two parallel wire sections of the connector receiving element include a conductive, non-corrosive coating, and wherein the insulated portion of the two parallel wire sections of the connector receiving member and the insulated portion of the two parallel wire sections of the connector receiving element include an electrically non-conductive coating.

Appl. No. 10/644,280  
Amdt. dated Mar. 21, 2006  
Reply to Off. Act. dated Dec. 23, 2005

Claim 16 (previously presented): The cable tray system of claim 12, wherein the fastener comprises a carriage bolt and a nut and wherein the two parallel wire sections of the connector receiving member are separated so as to receive and snugly engage a head of the carriage bolt such that rotation of the carriage bolt is prevented during threading of the nut onto the carriage bolt.

Claim 17 (previously presented): The cable tray system of claim 12, wherein the fastener comprises a carriage bolt and a nut and wherein the two parallel wire sections of the connector receiving element are separated so as to receive and snugly engage a head of the carriage bolt such that rotation of the carriage bolt is prevented during threading of the nut onto the carriage bolt.

Claim 18 (previously presented): The cable tray system of claim 12, wherein the fastener is electrically conductive.

Claims 19-23 (cancelled)

Claim 24 (previously presented): A cable tray for use in a cable tray system in which at least two cable trays are connected together with at least one fastener, the cable tray comprising:

a cable support assembly having a weight-bearing base portion and a plurality of sidewalls, the sidewalls being connected to longitudinal edges of the base portion and extending in a common direction perpendicular to the base portion, the base portion defining a plurality of open ends of the cable support assembly; and

a connector receiving member integrated into a sidewall of the cable support assembly proximate an open end of the cable support assembly, the connector receiving member including two parallel sections separated by a space and extending transversely across at least part of a width of the sidewall, the two parallel sections of the connector receiving member being arranged to at least receive at least a portion of a fastener in the space therebetween, wherein at least one of the two parallel sections of the connector receiving member includes an insulated

Appl. No. 10/644,280  
Amdt. dated Mar. 21, 2006  
Reply to Off. Act. dated Dec. 23, 2005

portion and an electrically conductive portion, and wherein the electrically conductive portion is arranged to engage the portion of the fastener.

Claims 25-27 (cancelled)

Claim 28 (previously presented): The cable tray system of claim 12, wherein the connector receiving member of the first cable tray is integrated into the base portion or the sidewall of the first cable support assembly.

Claim 29 (previously presented): A cable tray system comprising:

a first cable tray including a first cable support assembly and a connector receiving member, the first cable support assembly having a weight-bearing base portion and a plurality of sidewalls, the sidewalls of the first cable support assembly being connected to longitudinal edges of the base portion of the first cable support assembly and extending in a common direction perpendicular to the base portion of the first cable support assembly, the base portion of the first cable support assembly defining a plurality of open ends of the first cable support assembly, the connector receiving member being connected to at least one of the base portion and a sidewall of the first cable support assembly proximate an open end of the first cable support assembly, the connector receiving member including an insulated portion and an electrically conductive, contact portion, wherein the electrically conductive, contact portion of the connector receiving member defines an open space therein;

a second cable tray including a second cable support assembly and a connector receiving element, the second cable support assembly having a weight-bearing base portion and a plurality of sidewalls, the sidewalls of the second cable support assembly being connected to longitudinal edges of the base portion of the second cable support assembly and extending in a common direction perpendicular to the base portion of the second cable support assembly, the base portion of the second cable support assembly defining a plurality of open ends of the second cable support assembly, the connector receiving element being connected to at least one of the base portion and a sidewall of the second cable support assembly proximate an open end of the second cable support assembly, the connector receiving element including an insulated portion

Appl. No. 10/644,280  
Amdt. dated Mar. 21, 2006  
Reply to Off. Act. dated Dec. 23, 2005

and an electrically conductive, contact portion, the electrically conductive, contact portion of the connector receiving element defining an open space therein, wherein the electrically conductive, contact portion of the connector receiving element of the second cable tray overlaps the electrically conductive, contact portion of the connector receiving member of the first cable tray when the first cable tray and the second cable tray are positioned adjacent one another; and

a fastener adapted to pass through the open space defined by the connector receiving member of the first cable tray and the open space defined by the connector receiving element of the second cable tray to secure the electrically conductive, contact portion of the connector receiving member of the first cable tray to the electrically conductive, contact portion of the connector receiving element of the second cable tray, thereby providing electrical continuity between the first cable tray and the second cable tray.

Claim 30 (previously presented): The cable tray system of claim 29, wherein the insulated portion of the connector receiving member of the first cable tray comprises a non-conductive covering disposed upon a first conductive material and is substantially larger than the electrically conductive, contact portion of the connector receiving member, wherein the insulated portion of the connector receiving element of the second cable tray comprises a non-conductive covering disposed upon a second conductive material and is substantially larger than the electrically conductive, contact portion of the connector receiving element, and wherein the insulated portions of the connector receiving member and the connector receiving element isolate the first conductive material and the second conductive material from cables passed through the first cable tray and the second cable tray.